



breathaudio™

elevate

System Specifications

Power Amplifier Section

Continuous Average Output Power	15W
Two channels driven, 30–20kHz	@ 1% THD
Rated Distortion (1/2 power)	0.40%
Rated Impedance	8 Ohms
Damping Factor	50+
Frequency Response (30–20kHz)	+/- 3dB

Preamplifier Section

Input Impedance	50k
Input Sensitivity for rated power	330mV RMS
Input Overload	3V RMS

IR System

Source Outputs	2
Output Drive Current	50mA
Output Drive Voltage	12V
Compatible with single and dual emitters	

NuVo reserves the right to change specifications without notice.

Power Requirements

Power Supply	120VAC/240VAC 50/60Hz
Power Consumption all channels driven to full-rated power	190VA (166W)
Power Consumption average operating conditions	88VA (70W) 1/8 power
Power Consumption no signal	14VA (10W)
USA Safety Listing	ANSI/UL-6500

Physical Specifications

Unit Size Millimeters	89 x 216 x 325
Unit Size Inches	3.5 x 8.5 x 12.75
Shipping Size Millimeters	190 x 305 x 394
Shipping Size Inches	7.5 x 12 x 15.5
Unit Weight Kilograms	3.5
Unit Weight Pounds	7.8
Shipping Weight Kilograms	5
Shipping Weight Pounds	11.8